

**Control unit e.g. for motor vehicle electric windows, anti-theft warning and locks**

**Publication number:** DE19530721 (A1)

**Publication date:** 1997-02-20

**Inventor(s):** JAHRSETZ ACHIM [DE]; KLEEFELDT FRANK [DE];  
OSTERMANN WILFRIED [DE]; WELSKOPF FRED [DE]

**Applicant(s):** KIEKERT AG [DE]

**Classification:**

**- international:** E05F15/10; B60R16/02; B60R25/10; E05B65/12; E05B65/36;  
G08B13/00; H02J7/00; H02J9/06; H02J13/00; H04B1/59;  
B60R16/03; E05B47/00; E05F15/10; B60R16/02; B60R25/10;  
E05B65/12; E05B65/36; G08B13/00; H02J7/00; H02J9/06;  
H02J13/00; H04B1/59; B60R16/03; E05B47/00; (IPC1-  
7): H02J9/04; B60J1/20; B60R16/02; B60R25/10; E05B65/12;  
H04Q9/00

**- European:** B60R25/10F; E05B65/36B; H02J9/06

**Application number:** DE19951030721 19950818

**Priority number(s):** DE19951030721 19950818

**Also published as:**

US5736793 (A)

JP9137656 (A)

ITM1961390 (A1)

FR2737872 (A1)

**Abstract of DE 19530721 (A1)**

The motor vehicle (1) possesses a control installation with control equipment (2) connected to ancillary units by a multiplex single-wire bus (3). These units include door locks (4,13), window opening mechanism (5) and an anti-theft device (6), all provided with an actuating element (7) and connected to the control equipment by remote actuating units, such as a transmitter (8) and a receiver (9). The control installation is normally coupled to the starter battery (10) and, as mentioned above, to the emergency battery (11) by the emergency driving circuit (12) if needed.

